MEMORANDUM

TO	DATE	INITIAL	DATE
RETURN TO		FILE	

TO: Herbert A. Tessler, Supervisor, Funct. Coord.

FROM: Irv Soffer

DATE: December 2, 1964

SUBJECT: THE WORLD TRADE CENTER - TOWER FIREPROOFING

REFERENCE:

COPY TO: Messrs. L. Held, M. Levy, C. Panero

On Monday, November 23, 1964, I attended a meeting at Emery Roth & Sons with Joe Solomon and Ed Kister. Mr. Kister represents the Allegheny Ludlum Steel Corp., manufacturer of stainless steel, who are preparing a stainless steel exterior wall design for the World Trade Center. They are interested in proposing a package for the whole exterior treatment including spandrel fireproofing and windows from Adams and Westlake.

Allegheny is showing development done by Battelle Memorial Institute also with the Schlueter Co., manufacturer of precast concrete products. They are proposing a relatively thin precast, high density concrete jacket for the exterior column fireproofing.

They still have an Underwriter Laboratory Test performed on a simulated WTC column, then a full scale model will be built and additional tests made on it. The column fire test will be done by January, 1965. We expressed our interest in any new developments which might have WTC application.

Mr. Kister will confer with his group to determine a budget price for their package. He feels that they can be competitive.

On November 19, 1964 I met with Mr. Gerald Caplon of the Zonolite Co., manufacturers of Mono-Kote fireproofing. We inspected some of the installations in the Construction Yard at Mulberry Street, Bloomfield, Connecticut.

One application was for the large roof trusses at the Data Processing Center for the Travelers Insurance Company. 'Mono-Kote' is a cementitious mixture that is considerably better than the mineral fiber spray-on (which is very difficult to install). Although the mineral fiber is less expensive it is probable that a better price can be negotiated for 'Mono-Kote'. We inspected a 'Mono-Kote' application on steel floor beams, and a mineral fiber application on floor beams. Although they both provide the fire rating required, it was obvious that the 'Mono-Kote' was a better application. Photos were taken and are being circulated.

Another material being considered for truss fireproofing is 'Vonco'. This is a sprayed-on cementitious gypsum material, that is less than 1" thick, and hard finished. The U.S. Gypsum Co. is testing a similar material for truss fire-proofing. They are presently having WTC floor trusses built for tests in the next few weeks.

Irv Soffer
The World Trade Center

PA LAW DEPARTMENT
58857